

POLYURETHANE ROLL- / SELFLEVELING COATINGS





TACTICAL
— SUPPLY PAKISTAN —

EUROPUR 0500

EUROPUR 0500 is a solvent-free, pigmented 2-component flow coating based on polyurethane liquid resin, which is characterised by its excellent UV resistance and elasticity. This high-quality coating provides an attractive, seamless surface that is not only aesthetically pleasing, but also offers optimum protection against the weather. EUROPUR 0500 is ideal for applications where both durability and visual appeal are required, making it an excellent choice for modern design solutions.

APPLICATION AREAS

- For indoor and outdoor use
- as a coating for balconies, terraces and arcades
- Surface coating for concrete, cement screed, ceramic tiles, asphalt, etc.

PRODUCT FEATURES

- UV and colourfast
- Weatherproof
- Good mechanical properties
- Good chemical resistance
- decorative



AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
VISCOSITY AT +23°C	7000 - 11000 mPas
SEALS	approx. 1.6 g/cm³
DURABILITY	Weather-resistant good chemical resistance
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Object and processing temperatures min. 15 max. 30 °C
MIXING RATIO	A : B = 4 : 1
PROCESSING TIME	60 min

CONTENTS	Item number
5 KG	400500XXXXEK005
10 KG	400500XXXXEK010
30 KG	400500XXXXEK030





TACTICAL
— SUPPLY PAKISTAN —

EUROPUR 0510

EUROPUR 0510 is a solvent-free, pigmented 2-component gradient coating based on polyurethane liquid resin, which is characterised by its outstanding UV resistance and elasticity. This innovative coating makes it possible to create appealing, seamless surfaces with an attractive colour gradient that is both aesthetically pleasing and functional. EUROPUR 0510 not only provides effective protection against the elements, but also ensures a durable and resistant surface that is ideal for modern applications in various areas.

APPLICATION AREAS

- For indoor and outdoor use as a coating for balconies, terraces and arcades
- Surface coating for concrete, cement screed, ceramic tiles, asphalt, etc.
- Very suitable for use in sensitive areas such as schools and hospitals

PRODUCT FEATURES

- UV and colourfast
- Weatherproof
- Good mechanical properties
- Good chemical resistance
- decorative low emission



AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
VISCOSITY AT +23°C	7000 - 11000 mPas
TEMPERATURE RESISTANCE	from -40 to +120°C
CHEMICAL RESISTANCE	Yes
DURABILITY	UV and colourfast good mechanical properties
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Object and processing temperatures min. 15 max. 30 °C
MIXING RATIO	A : B = 4 : 1
PROCESSING TIME	60 min

CONTENTS	Item number
5 KG	400510XXXXEK005
10 KG	400510XXXXEK010
30 KG	400510XXXXEK030



EUROPUR 0520

EUROPUR 0520 is an economical, solvent-free 2-component polyurethane coating that is characterised by its self-levelling properties. This high-quality coating ensures a smooth and even surface that is both functional and aesthetically pleasing. EUROPUR 0520 not only offers effective protection against mechanical stress and chemical influences, but is also easy to apply, making it an ideal choice for a wide range of applications.

APPLICATION AREAS

- is used in the industry on concrete and asphalt, z. e.g. in warehouses, production halls and canteens.

PRODUCT FEATURES

- solvent-free
- Self-levelling
- Good chemical and mechanical properties
- Pigmented, impact- and abrasion-resistant coating for indoor use
- UV exposure can cause a change in colour





TACTICAL
— SUPPLY PAKISTAN —

AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
VISCOSITY AT +23°C	7000 - 11000 mPas
CHEMICAL RESISTANCE	Yes
DURABILITY	UV and colour-fast, weather-resistant
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Object and processing temperatures min. 15 max. 30 °C
MIXING RATIO	A : B = 4 : 1
PROCESSING TIME	60 min

CONTENTS	Item number
5 KG	400520XXXXEK005
10 KG	400520XXXXEK010
30 KG	400520XXXXEK030





TACTICAL
— SUPPLY PAKISTAN —

EUROPUR 0540

EUROPUR 0540 is a solvent-free, self-levelling 2-component polyurethane coating that is characterised by its outstanding processing properties and durability. This coating provides a smooth, even surface that is not only aesthetically pleasing, but also resistant to mechanical stress and chemical influences. EUROPUR 0540 is ideal for various applications where a hard-wearing and visually attractive solution is required and ensures easy processing for a first-class result.

APPLICATION AREAS

- is used in the industry on concrete and asphalt, z. e.g. in warehouses, production halls and canteens.

PRODUCT FEATURES

- solvent-free
- Self-levelling
- Good chemical and mechanical properties
- Pigmented, impact- and abrasion-resistant coating for indoor use
- UV exposure can cause a change in colour
- high quality





TACTICAL
— SUPPLY PAKISTAN —

AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
NUMBER OF COMPONENTS	2
MATERIAL CONSUMPTION	2,5 kg/m ²
SEALS	1,6 g/cm ³
CHEMICAL RESISTANCE	Yes
DURABILITY	Pigmented, impact and abrasion resistant
SELF-LEVELLING	Yes
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Processing temperature +15 to +25 °C
MIXING RATIO	A : B = 4 : 1
PROCESSING TIME	approx. 30 min

CONTENTS	Item number
5 KG	400540XXXXEK005
10 KG	400540XXXXEK010
30 KG	400540XXXXEK030





TACTICAL
— SUPPLY PAKISTAN —

EUROPUR 0560

EUROPUR 0560 is a highly elastic, solvent-free 2-component polyurethane coating that is characterised by its economical application and self-levelling properties. This innovative coating ensures an even and smooth surface that is both durable and resistant to mechanical loads. EUROPUR 0560 offers excellent flexibility, making it ideal for various applications where a hard-wearing and aesthetically pleasing solution is required. The ease of processing rounds off the overall package and makes the EUROPUR 0560 the ideal choice for demanding projects.

APPLICATION AREAS

- is used in the industry on concrete and cement z. For example, it is used in warehouses and production halls, canals, etc. and as a liquid sealant for stone carpets.

PRODUCT FEATURES

- solvent-free
- Self-levelling
- highly elastic
- Seals microcracks
- Noise-damping
- comfortable
- Good chemical and mechanical properties
- Pigmented, impact- and abrasion-resistant coating for indoor use
- UV exposure can cause a change in colour





TACTICAL
— SUPPLY PAKISTAN —

AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
MATERIAL CONSUMPTION	2,5 kg/m ²
DENSITY AT 23°C/50% R.H.	1,4 g/cm ³
NUMBER OF COMPONENTS	2
MATERIAL TEMPERATURE	+15 to +25 °C
DURABILITY	Resistant to ageing
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Processing temperature +15 to +30 °C
MIXING RATIO	A : B = 5 : 1
PROCESSING TIME	approx. 30 min

CONTENTS	Item number
5 KG	400560XXXXEK005
10 KG	400560XXXXEK010
30 KG	400560XXXXEK030





TACTICAL
— SUPPLY PAKISTAN —

EUROPUR 0580

EUROPUR 0580 is a robust, solvent-free 2-component polyurethane coating that is characterised by its economical application and self-levelling properties. This hard-wearing coating provides an even, smooth surface that guarantees optimum protection against mechanical and chemical stresses. EUROPUR 0580 is ideal for a wide range of applications where both durability and ease of application are required. With its outstanding resistance and attractiveness, this coating is a reliable solution for demanding projects

APPLICATION AREAS

- is used in the industry on concrete and asphalt, z. e.g. in warehouses and production halls, canteens, etc.

PRODUCT FEATURES

- solvent-free
- Self-levelling
- robust
- Good chemical and mechanical properties
- tough, hard, impact- and abrasion-resistant coating for indoor use
- UV exposure can cause a change in colour





TACTICAL
— SUPPLY PAKISTAN —

AT A GLANCE

COLOUR	Standard and special colours
MATERIAL BASIS	Polyurethane
MATERIAL CONSUMPTION	2,5 kg/m ²
SEALS	1,76 g/cm ³
NUMBER OF COMPONENTS	2
CHEMICAL RESISTANCE	Yes
DURABILITY	Robust, tough, impact- and abrasion-resistant coating
SELF-LEVELLING	Yes
STORAGE AND SHELF LIFE	Cool and dry, +10°C to +25°C, 12 months in unopened original container
PROCESSING CONDITIONS	Processing temperature +15 to +25 °C
MIXING RATIO	A : B = 6,88 : 1

CONTENTS	Item number
5 KG	400580XXXXEK005
10 KG	400580XXXXEK010
30 KG	400580XXXXEK030

